

DEVERAUX SERIES TABLES

By Jasper Library Furniture

TABLE TOP: The tops shall be 1-3/16" thick, 3-ply particle board core construction with a .050" thick high pressure laminate top surface and a .gator ply backing sheet. The tops shall have a solid hardwood 1-3/16" thick x 13/16" wide internal edgeband with a variety of shapes available. Veneer tops are an option.

APRON RAIL: The apron rail shall be constructed of 3" wide x 13/16" thick solid oak or maple with a 3/16" radius on the bottom edge. The connection of the apron rails to the legs shall provide an integral space frame construction. All four apron rails shall be arched to be 1" at the center to ensure **ADA compliance**.

LEGS: The legs shall be constructed of glued up solid oak or maple and shall be 2-1/4" square. All vertical edges shall be eased.

CONSTRUCTION: The aprons shall attach to the tops using 1-1/2" wood screws. The legs attach to the aprons with two 3-1/2" lag bolts passing through a solid oak corner block and tightened with lock washers and hex nuts.

TABLE HEIGHT: The standard table top height shall be 30". Additional heights of 27" and 25" are available when specified.

GLIDES: Each leg shall be fitted with one 1-3/16" diameter rubber cushioned adjustable leveling glide with a 15/16" stem.

LUMBERCORE TABLE TOP: Lumbercore table tops are available when specified.
